



HUSQVARNA TC 130

The TC 130 is a user-friendly tractor ideal for homeowners having small to mid-size gardens. It is a compact-sized, efficient tractor with integrated collector, smart design and ergonomics. Has a powerful Husqvarna Series engine with choke less start. Easy to manoeuvre thanks to its compact format and pedal-operated hydrostatic transmission. Can be fitted with a BioClip® plug.



Adjustable sliding seat

Unique seat platform automatically changes height as seat is moved forward or rearward to optimize operator position.



Pedal-operated hydrostatic transmission

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control.

Large, wide rear tyres

Improved traction and less risk of damaging delicate ground.

Air Induction

Innovative Air Induction mowing system that draws clean air from the top and bottom of the deck, enhancing air flow which results in greater grass lift and superior cut.



FEATURES

- Large, wide rear tyres for improved traction
- Pedal-operated hydrostatic transmission
- Adjustable seat, while seated
- Air Induction; excellent cutting performance
- Cast front axle for superior stability
- Easy to get operating with automatic choke.
- Robust and durable steel chassis
- Step-through for easy mounting
- Hour meter with service minder
- Battery indicator with charger connection
- Deck Wash Port
- BioClip® plug available as accessory
- Large integrated collector; easy to empty
- Easy-access cutting height adjustment
- Compact design for operation in tight spaces
- Signal indication when collector is full
- Cup holder for refreshments while mowing
- Powder-coated deck for improved durability
- Dual draglinks for improved manoeuvrability
- First-class cutting deck; maximum performance
- Headlights for operation in dark conditions
- High specified oil filter, pressure lubrication, anti vibration system and automatic choke.
- Manual blade engagement
- Reverse Operating System (ROS) for safety
- Water hose connection for easy cleaning
- Safety switch under seat
- Easy to get operating with automatic choke.
- Deck Wash Port
- Pedal-operated hydrostatic transmission
- Compact design for operation in tight spaces
- Battery indicator with charger connection
- Can be fitted with year-round accessories
- Step-through for easy mounting
- Cup holder for refreshments while mowing
- Easy-access cutting height adjustment
- Manual blade engagement
- Large integrated collector; easy to empty
- Anti-scalp wheels
- Safety switch under seat
- Signal indication when collector is full
- Robust and durable steel chassis
- High specified oil filter, pressure lubrication, anti vibration system and automatic choke.
- Hour meter with service minder
- Adjustable seat, while seated
- Cast front axle for superior stability
- Water hose connection for easy cleaning
- BioClip® plug available as accessory
- Powder-coated deck for improved durability
- Large, wide rear tyres for improved traction
- Air Induction; excellent cutting performance
- Dual draglinks for improved manoeuvrability
- Headlights for operation in dark conditions
- First-class cutting deck; maximum performance
- Reverse Operating System (ROS) for safety

Technical Specifications	
BATTERY	
Battery capacity	28 Ah
Battery voltage	12 V
CAPACITY	
Net power at preset rpm	3300 rpm
Power output	13.05 kW
Turning radius, min	16 in
Uncut circle	131 cm
CERTIFICATIONS	
Commercial Warranty	90 Days
Homeowner Warranty	3 Years
DIMENSIONS	
Article gross weight	237229 g
Article net weight	181891 g
Base machine, height	100 cm
Base machine, length	222.0 cm
Base machine, width (chute down)	89 cm
Base machine, width (chute up)	82 cm
Base machine, width	89 cm
Collector volume	200 l
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Cutting width	76 cm
Seat back height	Medium 13"
Tyre dimensions, front	13X5-6
Tyre dimensions, rear	16X6.5-8
Tyre size, rear Diameter	16 in

Technical Specifications	
Tyre size, rear Width	6.5 in
Weight	176 kg
Wheel/rim size, front Diameter	6 in
Wheel/rim size, rear Diameter	8 in
Wheelbase	122 cm
ENGINE	
Cylinders	1
Cylinder displacement	508 cm ³
Engine cooling	Air
Engine name	Intek
Generator	3.5 A
Motor/engine manufacturer	Briggs & Stratton
Motor/engine model	Husqvarna Series M31R9
Transmission manufacturer	Hydro-Gear
Transmission model	T2
Transmission type	Hydrostatic
Fuel tank volume	5.7 l
Fuel tank volume	1.5 gal (US)
EQUIPMENT	
Air filter type	Auto-type Paper
Anti-scalp wheels	0
BioClip® kit	Available as accessory
BioClip® plug	Available as accessory
Blade engagement	Manual
Blade type	High Performance
Blades	1 pcs
Collector	Included
Cup holder	Yes
Cutting deck type	Stamped
Cutting Methods (filter)	Collecting, Mulching
Cutting methods	Collect/Mulch
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Drive method	Pedal-operated
Front-End Protection	Available as accessory
Gears forward	0 steps
Gears reverse	0 steps
Generator	3.5 A
Headlights	Yes
Hour meter type	Digital with pre-programmed service intervals
Powder-coated cutting deck	Yes
Seat type	13" high back
LUBRICANTS	
Engine lubrication type	Pressure with Oilfilter
Fuel consumption	333 g/kWh
Fuel tank location	Front
Oil capacity	1.42 l
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
Seat material	Vinyl
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	105 dB(A)
Sound pressure level at operators ear	85 dB(A)
Sound power level, measured	105 dB(A)
VIBRATIONS	
Vibration level seat	0.05 m/s ²
Vibration level steering wheel	2.54 m/s ²
PACKAGING	
Packaging height	877 mm
Packaging length	1905 mm
Packaging volume	1931.31 dm ³
Packaging width	1156 mm
Quantity in Master pack	1

