



HUSQVARNA 362M18

Husqvarna 362M18 is a powerful mister. The efficient fan provides excellent discharge and coverage performance. Adjustable nozzle for various applications.

High mixture coverage

The powerful engine and fan leads to efficient mixture coverage.



Comfortable harness

Comfortable padded harness.

Easier cold starting

Removes air from carburetor and fuel system for easy starting.



Smart Start®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



FEATURES

- Air purge for easier cold starting
- Comfortable padded harness
- High mixture coverage
- Smart Start® for easy starting
- High discharge performance

Technical Specifications	
CAPACITY	
Maximum power speed	7500 rpm
Mist drop size High	100 µm
Mist drop size Low	60 µm
Mixture tank volume	18 l
Power output	2.8 kW
DIMENSIONS	
Article gross weight	16435 g
Article net weight	12000 g
Coverage horizontally	12 m
Coverage vertically	12 m
Mixture tank volume	18 l
Weight	12 kg
ENGINE	
Cylinder bore	47.5 mm
Cylinder displacement	62 cm ³
Cylinder stroke	36 mm
Fuel tank volume	1.8 l
Power output	2.8 kW
Power source	Petrol
Power/fuel type	Petrol
Spark plug	NGK BPMR7A
EQUIPMENT	
Discharge: liquid	4 l/min
Discharge: liquid Capability	1.06 gal/min
Source system	PAID
LUBRICANTS	
Fuel consumption	491 g/kWh
Fuel tank volume	1.8 l
Power/fuel type	Petrol
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	515 mm
Packaging length	605 mm
Packaging volume	250.818 dm ³
Packaging width	805 mm
Quantity in Master pack	1