



## HUSQVARNA TF 120 2017-

Lightweight, versatile tiller for cultivating and refining garden-sized plots, planting trees or shrubs or ploughing furrows for plants. Robust, durable construction and chain transmission ensure longer life, while forward-rotating tines, easy operation and ergonomic design increase comfort, effectiveness and productivity.



### Foldable handlebar

For easy storage and transport.



### Adjustable handlebar

Adjustable handlebar for best working position.

### Detachable transmission

Detachable transmission housing with lubrication nipple, for easy maintenance and service.

### Drag bar

Easy-adjust drag bar, for balance in different working conditions.



## FEATURES

- Detachable transmission for easy maintenance
- Adjustable handlebar for best working position.
- Easy foldable handlebar
- Drag bar for balanced operation
- Transport wheel for easy transport
- Moss rake available as accessory

Technical Specifications	
<b>CAPACITY</b>	
Net power at preset rpm	3150 rpm
Net power at preset rpm Energy	1.4 kW
Power output	1.4 kW
Rotational speed (min/max) max	140 rpm
Rotational speed (min/max) min	140 rpm
<b>DIMENSIONS</b>	
Article gross weight	31000 g
Article net weight	27000 g
Tine diameter	225 mm
Weight	27.0 kg
Working depth	15.0 cm
Working width	46.0 cm
<b>ENGINE</b>	
Cylinder displacement	79.0 cm <sup>3</sup>
Engine brand	RATO
Engine name	R80
Motor/engine manufacturer	RATO
Transmission steps forward	1
Transmission steps reverse	1
Transmission type	Chain/Manual
Transport wheel/s	2
Fuel tank volume	2 l
Fuel tank volume	0.53 gal (US)
<b>EQUIPMENT</b>	
Cultivator type	Front-tine
Drag bar	Yes
Foldable handlebar	Yes
Horizontally adjustable handlebar	No
Plant guards	No
Reverse gearbox	No
Transport wheel/s	2
Vertically adjustable handlebar	Yes
<b>LUBRICANTS</b>	
Fuel consumption	450 g/kWh
Fuel tank volume	2 l
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	93.0 dB(A)
Sound power level, measured	92.5 dB(A)
Sound pressure level at operators ear	84.0 dB(A)
<b>PACKAGING</b>	
Packaging height	500 mm
Packaging length	645 mm
Packaging volume	145.13 dm <sup>3</sup>
Packaging width	450 mm
Packaging, gross weight	32.0 kg
Quantity in Master pack	1
Quantity per pallet	16.0 pcs
Quantity per trailer	352.0 pcs