



HUSQVARNA TF 230

A basic and handy tiller that is easy to manoeuvre. Powered by a reliable and powerful Husqvarna engine and equipped with a bumper to protect the engine in use or during transportation. Foldable handlebar and transport wheel is standard. The fully sealed transmission makes it a perfect and long-lasting partner for work in wet cultures. This is a tiller for every customer who values durability and long-lasting efficiency.

Plant guard

Protect plants outside the working area.



Husqvarna gasoline engine

Powerful and reliable husqvarna gasoline engine.

Protective bumper

The bumper will protect the engine in use or during transportation. It can also serve as lifting handle.



Adjustable handlebar

Adjustable handlebar for best working position.



FEATURES

- The bumper will protect the engine in use or during transportation. It can also serve as lifting handle.
- Powerful and reliable husqvarna gasoline engine.
- Protect plants outside the working area.
- Adjustable handlebar for best working position.
- Large support wheel for easy maneuvering.

Technical Specifications	
CAPACITY	
Net power at preset rpm	3100 rpm
Net power at preset rpm Energy	3.45 kW
Power output	3.45 kW
Rotational speed (min/max) max	97 rpm
Rotational speed (min/max) min	53 rpm
DIMENSIONS	
Article gross weight	78500 g
Article net weight	66500 g
Tine diameter	320 mm
Weight	70 kg
Working depth	30 cm
Working width	75 cm
ENGINE	
Cylinder displacement	196 cm ³
Engine brand	Husqvarna
Engine name	Husqvarna Engine
Transmission steps forward	2
Transmission steps reverse	1
Transmission type	Chain/Manual
Transport wheel/s	1
Fuel tank volume	3.6 l
Fuel tank volume	0.95 gal (US)
EQUIPMENT	
Cultivator type	Front-tine
Drag bar	Yes
Foldable handlebar	Yes
Handlebar-mounted gear selection	No
Horizontally adjustable handlebar	No
Plant guards	Yes
Product Comment	For APAC, Russia and Ukraine only.
Reverse gearbox	Yes
Rubber wheels	Not available
Transport wheel/s	1
Vertically adjustable handlebar	Yes
LUBRICANTS	
Fuel consumption	395 g/kWh
Fuel tank volume	3.6 l
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	97 dB(A)
Sound power level, measured	95 dB(A)
Sound pressure level at operators ear	75 dB(A)
PACKAGING	
Packaging height	780 mm
Packaging length	845 mm
Packaging volume	316.37 dm ³
Packaging width	480 mm
Quantity in Master pack	1

ACCESSORIES



HUSQVARNA CONNECTING
BRACKET B-TYPE
588 26 60-01




HUSQVARNA POTATOES
HARVESTING PLOUGH
588 26 61-01



HUSQVARNA DITCHING BLADE
588 26 64-01



PLOUGH
588 26 67-01



HUSQVARNA METAL WHEEL KIT -
EMM
588 26 70-01



HUSQVARNA PADDY WHEEL KIT -
EMM
588 26 68-01



RUBBER WHEELS KIT
588 26 69-01