



## HUSQVARNA 372 XP®

A true professional saw in the larger mid-size class, built for very demanding applications. The crankcase and crankshaft are extra heavy-duty and the carburettor has vibration damping in order to handle high speeds and high loads. The saw combines low weight, high power and rapid acceleration with flexible operation. The XP® G model has both heated handles and carburettor.




### Quick-release air filter

Facilitates cleaning and replacement of the air filter.



### Adjustable oil pump

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.



### Air Injection®

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



### Side-mounted chain tensioner

Side-mounted chain tensioner makes chain adjustment quick and easy.



## FEATURES

- Less filter cleanings with Air Injection
- Adjustable chain oil pump
- Quick-release air filter
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Maximum durability for tough applications
- LowVib® sparing the user's arms and hands
- Smart Start® for easy starting
- Ergonomic grip with angled front handle
- Increased safety, inertia activated chain brake

### Technical Specifications

<b>CAPACITY</b>	
Chain speed at 133% of maximum engine power speed	28.5 m/s
Clutch engagement speed (±120)	3600 rpm
Clutch engagement upper limit	6000 rpm
Idling speed	2700 rpm
Idling upper limit	3500 rpm
Ignition module air gap	0.3 mm
Maximum power speed	9600 rpm
Power output	3.9 kW
Racing speed lower limit	12000 rpm
Torque, max.	4.3 Nm
Torque, max. at rpm	6600 rpm
<b>CERTIFICATIONS</b>	
Cert machine dir. 2006/42/EC Decl. No.	0404/09/2089
Recyclability, today	80 %
Recyclable of weight of FE, Al and Mg	45 %
<b>DIMENSIONS</b>	
Article gross weight	8908 g
Article net weight	7870 g
Bar length (inch)	18 in
Bar length	45 cm
Weight (excl. cutting equipment)	6.3 kg
<b>ENGINE</b>	
Carburetor	Walbro
Cylinder bore	50 mm
Cylinder displacement	70.7 cm <sup>3</sup>
Cylinder stroke	36 mm
Electrode gap	0.5 mm
Ignition module air gap	0.3 mm
Max engine/motor	13500 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
<b>EQUIPMENT</b>	
Bar mount type	Large
Chain type	H42
Chainsaw sub-group	Full time professional use chainsaws
Gauge	1.5 mm
Handle type	Standard
Pitch	3/8"
Source system	PAID
Sprocket type	Rim 7
<b>LUBRICANTS</b>	
Fuel consumption	480 g/kWh
Fuel consumption	1.9 kg/h
Fuel tank volume	0.77 l
Fuel type, min (Europe)	RON min 91 or alkylate
Lubricant type	Husqvarna or equiv. at 50:1
Oil pump capacity Max	21 ml/min
Oil pump capacity Min	4 ml/min
Oil pump type	Automatic
Oil tank volume	0.42 l
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>PACKAGING</b>	
Packaging height	250 mm
Packaging length	470 mm
Packaging volume	39.95 dm <sup>3</sup>

**Technical Specifications**

Packaging width	340 mm
Quantity in Master pack	1
<b>EMISSION DATA EPA</b>	
Exhaust emissions (CO average)	348.5 g/kWh
Exhaust emissions (CO average)	752.5 g/kWh
Exhaust emissions (HC average)	126 g/kWh
Exhaust emissions (NOx average)	2.3 g/kWh
<b>SOUND AND NOISE</b>	
Sound level	103 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Sound power level, measured	114 dB(A)
Sound pressure level at operators ear	103 dB(A)
<b>VIBRATIONS</b>	
Daily Vibration (Aeqv)	8.0 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	5.4 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	3.7 h
Equivalent vibration level (ahv, eq) front handle	5.7 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	8.0 m/s <sup>2</sup>