







Oil Immersed disc brakes



Smart 3D Seat



Side Shift Gears



Planetary Gear with Straight Axle





Technical Specifications

ENGINE

: John Deere 3029D, Type

> 40 HP (29.8 kW) 2100 RPM, Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single

Gear box : 8 Forward + 4 Reverse, Collarshift

: Forward 3.25 - 35.51 kmph Speeds Reverse 4.27 - 15.45 kmph

HYDRAULICS

Maximum Lifting capacity: 1600 kgf

3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

POWER TAKE OFF

: Independent, 6 Splines Type

: 540 @ 2100 ERPM Standard

WHEELS AND TYRES

: 6.0 X 16 (0.15m x 0.41m), 8 PR Front : 13.6 X 28 (0.34 x 0.71 m), 12 PR Rear

FUEL TANK

: 60 L Capacity

ACCESSORIES*

- Ballast weights Canopy Canopy holder
- Draw bar Tow hook Wagon hitch

FACTORY FITTED OPTIONS

 Roll over protection structure (ROPS) with deluxe seat and seat belt



FEATURES

- PTO NSS Underhood exhaust muffler Water separator
- Rear oil axle with metal face seal

Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner

Long life and less maintenance

High torque reserve

Ideal for heavy load applications

High torque across the operating speed range





Front Visibility



Digital Hour Meter



Finger guard



Oil Jet for Piston Cooling



Radiator with **Overflow Reservoir**





Top Shaft Lubrication



Dry Type Air Filter



Battery Inside Hood



International Looks (Automatic hood with lock)

John Deere **Genuine Parts**

I Economical I Reliable I Easily available I



John Deere India Private Limited


3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in











• Harvesters • Finance

