

TECHNICAL SPECIFICATIONS

ENGINE	
Туре	: John Deere 3029D, 40 HP (29.8 kW), 2100 RPM, Coolant cooled with overflow reservoir, Naturally aspirated
Air filter	: Dry type, Dual element
TRANSMISSION	
Clutch Gear box Speeds	: Single / Dual : 8 Forward + 4 Reverse, Collarshift : Forward 2.84 - 31.70 kmph Reverse 3.74 - 13.52 kmph
HYDRAULICS	
Maximum Lifting capac 3 point linkage	ity : 1600 kgf : Category - II Automatic depth and draft control (ADDC)
POWER TAKE OFF	
Type Standard	: Independent, 6 Splines : 540 @ 2100 ERPM
WHEELS AND TYRES	
Front Rear	: 8.0 X 18 (0.20 X 0.46 m), 8 PR : 13.6 X 28 (0.34 X 0.71 m), 12 PR
FUEL TANK	
Capacity	: 60 L

ACCESSORIES*

- Ballast weights Canopy Canopy holder
- Draw bar Tow hook Wagon hitch

FACTORY FITTED OPTIONS

• Roll over protection structure (ROPS) with deluxe seat and seat belt • Dual clutch

FEATURES

- PTO NSS Underhood exhaust muffler
- Water separator
- Front & Rear oil axle with metal face seal

Modern, technologically advanced, powerful John Deere 3029D engine

- Wet liner Long life and less maintenance
- High torque reserve Ideal for heavy load applications
- High torque across the operating speed range

2WD model is also available



20.6





Planetary Gear with Straight Axle **Finger Guard**







Radiator with **Overflow Reservoir**

Top Shaft Lubrication

5105 4WD 01 0720 ENG



Oil Jet for

Piston Cooling



Dry Type Air Filter Battery Inside Hood

Oil Immersed Disc Brakes

John Deere **Genuine Parts** I Economical I Reliable I I Easily available I



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.

Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.



• Tractors • Implements • Harvesters • Finance

