

With Higher
Lift Capacity

Ploughing or pulling, 5210 has the edge !



*Conditions apply.



Power Brakes
Self adjusting, self equalising,
hydraulically actuated,
oil immersed disc brakes



High torque reserve
Ideal for heavy load
applications



**Multipurpose
Heavy Duty Tractor**

*Zindagi ka
Best Decision!*TM



JOHN DEERE



Power Steering
Work hard. Drive smooth



Oil Jet for Piston Cooling



John Deere Powerful engine
Save more Fuel



Dry type air filter



Planetary Gear with Straight Axle
Low noise, less vibration, highly durable



Single piece hood opening with gas struts
The daily inspection and routine maintenance now made easy



Top Shaft Lubrication



Hood Lock
Totally Secure



Mobile Charging Point with Holder
Stay connected anytime

John Deere Genuine Parts

I Economical I Reliable I Easily available I



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013, Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.



TECHNICAL SPECIFICATIONS

ENGINE

Type	: 50 HP (37.3 kW), 2400 RPM, 3 Cylinders, Direct Injection, Turbo Charged, Inline FIP, Coolant cooled with overflow reservoir
Air filter	: Dry type, Dual element

TRANSMISSION

Clutch	: Dual
Gear box	: 9 Forward + 3 Reverse, Collarshift
Speeds	: Forward 2.1 - 30.1 kmph Reverse 3.6 - 23.3 kmph

BRAKES

	: Self adjusting and self equalising, Hydraulically actuated, Oil Immersed Disc Brakes
--	--

HYDRAULICS

Maximum Lifting capacity	: 2000 kgf
3 point linkage	: Category - II Automatic depth and draft control (ADDC)

STEERING

Type	: Power
------	---------

POWER TAKE OFF

Type	: Independent, 6 Splines
RPM	: 540 @ 2376 ERPM

WHEELS AND TYRES

Standard	: Front - 6 X 16 (0.15 x 0.41 m), 8 PR Rear- 14.9 X 28 (0.38 x 0.71 m), 12 PR
Optional	: Front - 7.5 X 16 (0.19 x 0.41 m), 8 PR/ 6.5 x 20 (0.17 x 0.51 m) Rear - 16.9 X 28 (0.43 x 0.71), 12 PR

FUEL TANK

Capacity	: 68 L
----------	--------

ELECTRICAL SYSTEM

	: 88 Ah, 12 V battery, 40 Amp. alternator, 12 V, 2.5 kW Starter motor
--	---

DIMENSIONS AND WEIGHT

Total weight	: 2105 kg
Wheel base	: 2050 mm
Overall length	: 3540 mm
Overall width	: 1820 mm
Ground clearance	: 0440 mm
Turning radius with brakes	: 3181 mm

ACCESSORIES*

- Ballast weights • Canopy • Tow hook • Canopy holder
- Draw bar • Wagon hitch

ADDITIONAL FEATURES

- Selective Control Valve (SCV)
- Adjustable Front Axle
- Heavy Duty Front Axle
- Reverse PTO (Standard + Reverse)
- Dual PTO (Standard + Economy)

- Tractors • Implements
- Harvesters • Finance

