TECHNICAL SPECIFICATION

		2WD	4WD
ENGINE		63 HP (46 kW), 2100 RPM, 3 cylinder, Direct injection, Turbo charged, Inline FIP, coolant cooled with over flow reservoir	
AIR FILTER		Dry type, dual element	
TRANSMISSION	Clutch	Dual	
	Gear Box	12 Forward + 4 Reverse, Collar Shift	
	Speeds	Forward 2.0 - 32.6 kmph Reverse 3.5 - 22.9 kmph	
BRAKES		Self Adjusting, Self Equalising, Hydraulically Actuated, Oil immersed disk brakes	
HYDRAULICS	Maximum Lifting capacity	2000 kgf	
	3 Point linkage	Category II, Automatic depth & draft control (ADDC)	
STEERING		Power Steering , Tilt steering [‡] : tiltable up to 25° with lock latch	
POWER TAKE OFF	Туре	Independent , 6 splines	
	RPM	Dual PTO Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM	
FUEL TANK CAPACITY		68 L	
WHEELS AND TYRES	Front	6.5 x 20 (0.17 x 0.51 m), 8 PR	11.2 x 24 (0.28 x 0.61 m), 8 PR 9.5 x 24 (0.24 x 0.61 m), 8 PR (Optional)
	Rear	16.9 x 30 (0.43 x 0.76 m), 12 PR 16.9 x 28 (0.43 x 0.71 m), 12 PR (Optional)	16.9 x 30 (0.43 x 0.76 m), 12 PR 16.9 x 28 (0.43 x 0.71 m), 12 PR (Optional)
ELECTRICAL SYSTEM		88 Ah, 12 V battery, 40 Amp. Alternator, 2.5 kW starter motor	
DIMENSIONS AND WEIGHT	Total weight Wheel base Overall length	2280 kg 2050 mm 3515 mm	2570 kg 2050 mm 3585 mm
	Overall width	1870 mm	1910 mm
	Ground clearance	0425 mm	0425 mm
	Turning radius with brakes	3181 mm	3181 mm
OPTIONAL ACCESSORIES		Ballast Weight	
#O-+:I f+			



FACTORY FITTED OPTIONS

- Adjustable front axle
- Heavy duty front axle
- Reverse PTO (Std + Reverse)
- Single PTO
- EQRL system
- Synchromesh Transmission (TSS)
- Selective Control Valve (SCV)

ADDITIONAL FEATURES

- Single piece hood with gas strut mechanism
- · Side bar, exhaust muffler guard & finger guard
- Water bottle holder
- Mobile charging point with holder
- Sway bar
- Seat with arm rest

Note: All the options / features may not be available in a single variant.

John Deere **Genuine Parts**

I Economical I Reliab I Easily available I



#Optional feature.


John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in For more information, please contact our authorised dealer or nearest area office.





















The 4 Range Tractor









JOHN DEERE











Mobile Charging
Point with Holder
Stay connected anytime



Power Brakes
Self adjusting, self equalising,
hydraulically actuated,
Oil immersed disc brakes



Hood Lock Totally secure



Planetary Gear with Straight Axle Low noise, less vibration, highly durable



Modern dashboard, with Digital Hour Meter and Combo-switch



Dry type air filter 99.9% clean air ensures longer engine li



Power Steering with Tilt Steering Work hard. Drive smooth.



Oil Jet for Piston Cooling



John Deere 3029H engine Powerful and fuel efficient



















