

Now with
Higher Lift Capacity

New
60 HP 4WD ^{44.7}_{kW}
Model 5060 E

Do Kadam Aage...



★
John Deere Promise
5 YEARS
WARRANTY*
— TECHNOLOGY LEADERSHIP —

*Conditions apply.



John Deere's New Powerful 3029H Turbo charged engine with Inline FIP



Dry type air filter Ease of maintenance and longer engine life



Power Steering



Hood Lock



Mobile Charging Point with Holder

*Zindagi ka
Best Decision!*



JOHN DEERE

New 60 HP ^{44.7 kW} 4WD Model 5060 E

TECHNICAL SPECIFICATIONS

ENGINE

Type	: 60 HP (44.7 kW), 2400 RPM, 3 Cylinders, Direct Injection, Turbo Charged, Inline FIP, Coolant cooled with over flow reservoir
Air filter	: Dry type, Dual element

TRANSMISSION

Clutch	: Dual
Gear box	: 9 Forward + 3 Reverse, Collarshift
Speeds	: Forward 2.05 - 28.8 kmph Reverse 3.45 - 22.33 kmph

BRAKES

: Self adjusting and self equalising,
Hydraulically actuated,
Oil Immersed Disc Brakes

HYDRAULICS

Maximum Lifting capacity	: 2000 kgf
3 point linkage	: Category - II Automatic depth and draft control (ADDC) Selective control valve (SCV)

STEERING

Type	: Power
------	---------

POWER TAKE OFF

Type	: Independent, 6 Splines
RPM	: 540 @ 2376 ERPM

WHEELS AND TYRES

Front	: 9.5 x 24 (0.24 x 0.61 m), 8 PR
Rear	: 16.9 x 28 (0.43 x 0.71 m), 12 PR

FUEL TANK

Capacity	: 68 L
----------	--------

ELECTRICAL SYSTEM

	: 88 Ah, 12 V battery, 43 Amp. alternator, 12 V, 2.5 kW Starter motor
--	---

DIMENSIONS AND WEIGHT

Total weight	: 2410 kg
Wheel base	: 2050 mm
Overall length	: 3580 mm
Overall width	: 1875 mm

ACCESSORIES*

- Ballast weights • Canopy • Canopy holder
- Draw bar • Wagon hitch

ADDITIONAL FEATURES / FACTORY FITTED OPTIONS

- Top shaft lubrication
- Collarshift transmission with helical gears
- Finger guard
- PTO Shield
- Dry type air filter
- Roll over protection system (ROPS)
with deluxe seat and seat belt

2WD model is also available

Note: All the options / features may not be available in a single variant.



Smart Brakes

Self adjusting, self equalising,
hydraulically actuated,
oil immersed disc brakes



Automatic Hood Opening

Single piece hood opening
with gas struts




High Torque Reserve ~ 40%

Ideal for heavy load
applications



Side Bar & Steps

Climbing up and down
the tractor is now easier



Oil Jet for Piston Cooling



Engine Oil Cooler



International looks with Gun Sight



Planetary Gear with Straight Axle



4 Wheel Drive

John Deere Genuine Parts

| Economical | Reliable |
| Easily available |



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar,
Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.



- Tractors • Implements
- Harvesters • Finance



JOHN DEERE