



HUSQVARNA 143R-II

Husqvarna 143R-II is a rugged brushcutter designed for tough use. The handle bar has an asymmetrical design which leads to better working position. Delivered with double harness.



Combi-guard

The cutting attachment combi-guard can be used with either a grass blade or a trimmer head.



Easier cold starting

Removes air from carburetor and fuel system for easy starting.

Standard double harness

Standard harness for lighter brushcutters.



Robust handle system

The handle bar is attached to the tube by a die casted clamp for high durability.



FEATURES

- Standard harness for lighter brushcutters
- Air purge for easier cold starting
- Versatile use with combi guard
- Robust handle system
- Heavy duty clutch
- Easy to service and maintain starter
- Efficient air filter
- Grass bevel gear for best cutting performance

Technical Specifications

CAPACITY

Clutch engagement speed (± 120)	3300 rpm
Idling speed	2500 rpm
Maximum power speed	7500 rpm
Power output	1.5 kW
Torque, max.	2.3 Nm
Torque, max. at rpm	5500 rpm

DIMENSIONS

Article gross weight	12300 g
Article net weight	10500 g
Cutting width	27.5 cm
Tube diameter	28 mm
Tube length	1483 mm
Weight (excl. cutting equipment)	7.6 kg

ENGINE

Cylinder bore	40 mm
Cylinder displacement	41.5 cm ³
Cylinder stroke	33 mm
Electrode gap	0.6 mm
Gear ratio	1
Ignition module air gap	0.3 mm
Spark plug	NGK BPMR7A

EQUIPMENT

Drive gear angle	30 °
Grass blade	Multi 275-4
Harness	Standard double harness
Saw blade	Not included
Trimmer head	T45X M12

LUBRICANTS

Fuel consumption	653 g/kWh
Fuel tank volume	0.94 l
Power/fuel type	Gasoline

MATERIALS

Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g

PACKAGING

Box Print	1 Color Print (Brown Box)
Packaging height	125 mm
Packaging length	1670 mm
Packaging volume	71.06 dm ³
Packaging width	125 mm
Quantity in Master pack	1

SOUND AND NOISE

Sound power level, guaranteed (LWA)	113 dB(A)
Sound pressure level at operators ear	99 dB(A)

VIBRATIONS

Equivalent vibration level (ahv, eq) left handle	5.1 m/s ²
Equivalent vibration level (ahv, eq) right handle	6 m/s ²